



---

Managed by Fermi Research Alliance, LLC for the U.S. Department of Energy Office of Science

---

# **File Invalidation Proposal draft**

Natalia Ratnikova

CMS transfer team chat

28 April 2016

# Goals

---

- Automate the process of file invalidations
- Minimize risk of loosing any useful data
- Build on top of existing operations procedures, infrastructure and tools

## Two types of invalidations

---

- **Local invalidation:** unregister file replica at the site
  - file replica is deleted from TMDB
  - PhEDEx download agent at the site will try to re-transfer the file as long as dataset/block are still subscribed
- **Global invalidation:** involves DBS
  - all replicas are locally invalidated
  - file is assigned invalid status in DBS

## Examples

---

1. File is valid in DBS, but has no replica at any site
2. File replica is missing or corrupted on storage
  - detected by the BDV check
  - found by transfer team operators by analyzing logs for repeatedly failing transfers
  - reported lost/corrupted by the site storage facilities

## Considerations

---

- To minimize the risk of data loss, we try to keep operations on the level of data catalogs (TMDB, DBS) and avoid actions on the storage side

# Proposal

---

1. Enable “*garbage collection*” by a central agent that will
  - detect files with zero replicas
  - publish a list of such files for global invalidation in DBS
2. Enable **local invalidation**
  - harvest BDV agent results for the sites and invalidate local replicas for files failing the checks to trigger retransfer
3. Extend the BlockDownloadVerifyInjector agent to **inject BDV checks** for the blocks containing repeatedly failing files
4. Site admins update storage catalogs tests for missing/corrupted file (remove if necessary) and **inject BDV checks**
5. Files invalidated locally but remaining on storage will be detected by **StorageConsistencyCheck**

**Comments ...**  
**Suggestions ...**